```python
# Stores a name in a variable

name = input("What's your name? ")
print(f"hello, {name}")
```

```python
# Stores names in a list

names = []

for _ in range(3):
    names.append(input("What's your name? "))

for name in sorted(names):
    print(f"hello, {name}")
```

```
1    Hermione
2    Harry
3    Ron
4    Draco
```

```
1  # Writes to a file
2
3  name = input("What's your name? ")
4
5  file = open("names.txt", "w")
6  file.write(name)
7  file.close()
```

```python
# Appends to a file

name = input("What's your name? ")

file = open("names.txt", "a")
file.write(f"{name}\n")
file.close()
```

```python
# Adds context manager

name = input("What's your name? ")

with open("names.txt", "a") as file:
    file.write(f"{name}\n")
```

```python
# Reads from a file

with open("names.txt") as file:
    lines = file.readlines()

for line in lines:
    print("hello,", line.rstrip())
```

```
1  # Reads from a file, one line at a time
2
3  with open("names.txt") as file:
4      for line in file:
5          print("hello,", line.rstrip())
```

```python
# Appends names to a list for sorting

names = []

with open("names.txt") as file:
    for line in file:
        names.append(line.rstrip())

for name in sorted(names):
    print(f"hello, {name}")
```

```
1   Hermione,Gryffindor
2   Harry,Gryffindor
3   Ron,Gryffindor
4   Draco,Slytherin
```

```python
# Reads a CSV file

with open("students0.csv") as file:
    for line in file:
        row = line.rstrip().split(",")
        print(f"{row[0]} is in {row[1]}")
```

```python
1  # Unpacks a list
2
3  with open("students0.csv") as file:
4      for line in file:
5          name, house = line.rstrip().split(",")
6          print(f"{name} is in {house}")
```

```
1   # Sorts a list of strings
2
3   students = []
4
5   with open("students0.csv") as file:
6       for line in file:
7           name, house = line.rstrip().split(",")
8           students.append(f"{name} is in {house}")
9
10  for student in sorted(students):
11      print(student)
```

```python
# Reads a CSV file into a list of dict objects, creating empty dict first

students = []

with open("students0.csv") as file:
    for line in file:
        name, house = line.rstrip().split(",")
        student = {}
        student["name"] = name
        student["house"] = house
        students.append(student)

for student in students:
    print(f"{student['name']} is in {student['house']}")
```

```python
# Reads a CSV file into a list of dict objects, creating dict first

students = []

with open("students0.csv") as file:
    for line in file:
        name, house = line.rstrip().split(",")
        student = {"name": name, "house": house}
        students.append(student)

for student in students:
    print(f"{student['name']} is in {student['house']}")
```

```python
# Reads a CSV file into a list of dict objects

students = []

with open("students0.csv") as file:
    for line in file:
        name, house = line.rstrip().split(",")
        students.append({"name": name, "house": house})

for student in students:
    print(f"{student['name']} is in {student['house']}")
```

```python
# Sorts a list of dictionaries using a function

students = []

with open("students0.csv") as file:
    for line in file:
        name, house = line.rstrip().split(",")
        students.append({"name": name, "house": house})


def get_name(student):
    return student["name"]


for student in sorted(students, key=get_name):
    print(f"{student['name']} is in {student['house']}")
```

```python
# Sorts a list of dictionaries using a lambda function

students = []

with open("students0.csv") as file:
    for line in file:
        name, house = line.rstrip().split(",")
        students.append({"name": name, "house": house})

for student in sorted(students, key=lambda student: student["name"]):
    print(f"{student['name']} is in {student['house']}")
```

```
1   Harry,"Number Four, Privet Drive"
2   Ron,The Burrow
3   Draco,Malfoy Manor
```

```python
# Reads a CSV file using csv.reader

import csv

students = []

with open("students1.csv") as file:
    reader = csv.reader(file)
    for row in reader:
        students.append({"name": row[0], "home": row[1]})

for student in sorted(students, key=lambda student: student["name"]):
    print(f"{student['name']} is from {student['home']}")
```

```
1  name,home
2  Harry,"Number Four, Privet Drive"
3  Ron,The Burrow
4  Draco,Malfoy Manor
```

```python
1   # Reads a CSV file using csv.DictReader
2
3   import csv
4
5   students = []
6
7   with open("students2.csv") as file:
8       reader = csv.DictReader(file)
9       for row in reader:
10          students.append({"name": row["name"], "home": row["home"]})
11
12  for student in sorted(students, key=lambda student: student["name"]):
13      print(f"{student['name']} is from {student['home']}")
```

```python
1   # Writes a CSV file using csv.writer
2
3   import csv
4
5   name = input("What's your name? ")
6   home = input("Where's your home? ")
7
8   with open("students2.csv", "a") as file:
9       writer = csv.writer(file)
10      writer.writerow([name, home])
```

```python
# Writes a CSV file using csv.DictWriter

import csv

name = input("What's your name? ")
home = input("Where's your home? ")

with open("students2.csv", "a") as file:
    writer = csv.DictWriter(file, fieldnames=["name", "home"])
    writer.writerow({"name": name, "home": home})
```

```python
# Opens and saves binary files

import sys

from PIL import Image

images = []

for arg in sys.argv[1:]:
    image = Image.open(arg)
    images.append(image)

images[0].save(
    "costumes.gif", save_all=True, append_images=[images[1]], duration=200, loop=0
)
```